


Goalrilla™

72" BACKBOARD, FIXED HEIGHT BASKETBALL SYSTEM

MODEL NO.
B4800W

**PROFESSIONAL
INSTALLATION ONLY!**



**Please Do Not Return This
Product to the Store!**

Contact Escalade® Sports customer service department at:
Phone: 1-888-USA-GOAL Toll-Free!
Fax: 1-866-873-3536 Toll-Free!
E-mail: customerservice@escaladesports.com

ESCALADE®
SPORTS

2L-7987-00

2022 Escalade® Sports

PRE-ASSEMBLY TIPS

1. **Read this manual carefully before starting assembly.** Read each step completely before beginning each step.
2. **Some smaller parts may be shipped inside larger parts.** Check inside all parts and cartons before assembling or ordering parts.
3. **To make assembly easier, use the Parts List and Hardware Identifier on pages 4, 5, 6, & 7 to identify and sort all components.** Check all cartons for kits. All hardware may not be located in one kit.
4. **Do not tighten hardware until instructed to do so.** If hardware is tightened too soon, mounting holes may not align and parts may not easily fit together. Leave locknuts slightly loose until you are instructed to tighten them.
5. **An electric screwdriver is helpful in assembly.** However, please set at low torque and use caution because you could overtighten the hardware and strip the screws.
6. **Save these instructions and your proof of purchase (receipt) in the event that the manufacturer has to be contacted for replacement parts.**

Tools required for assembly:

- | | |
|--------------------------------------|-------------------------------------|
| 1 - 3/8" Drive Ratchet | 1 - Phillips Screwdriver |
| 1 - 15/16" open end wrench | 1 - Level |
| 1 - 15/16" socket and ratchet | 1 - Tape Measure |
| 1 - 9/16" Deep Well Socket & Ratchet | 1 - 5/16" Hex Key Socket (included) |
| 1 - 3/4" Socket & Ratchet | 1 - 1/2" Drive Torque Wrench |
| 1 - 3/4" Open end Wrench | min 90ft/lbs |
| | 1 - 1/2" Drive Ratchet |
| | 1 - Needle Nose Pliers |

Please visit our Website at:

www.Goalrilla.com

ON-LINE TROUBLE SHOOTING TECHNICAL ASSISTANCE
PRODUCT REGISTRATION FREQUENTLY ASKED QUESTIONS
ADDITIONAL GOALRILLA PRODUCT INFORMATION



Please Do Not Return This Product To The Store!

Contact Escalade® Sports customer service department at:

Phone: 1-800-467-1421 **Toll – Free !**

E-mail: basketball@escaladesports.com

Escalade Sports

Physical Location:

817 Maxwell Ave.
Evansville, IN 47711

Mailing Address: (Correspondence Only)

PO Box 889
Evansville, IN 47706

ESCALADE®
S P O R T S

WARNING

FAILURE TO FOLLOW THESE WARNINGS MAY RESULT IN SERIOUS INJURY AND/OR PROPERTY DAMAGE.

Owner must ensure that all players know and follow these rules for safe operation of the system.

- Only hang from the rim briefly to regain balance or avoid injuring others. Release the rim as soon as safely possible.
- DO NOT HANG on the rim or any part of system including backboard, support braces or net.
- During play, especially when performing dunk type activities, keep players face away from the backboard, rim, and net. Serious injury could occur if teeth/face encounter backboard, rim, or net.
- Wear a mouthguard when playing to avoid dental injuries.
- Do not slide, climb, or play on pole.
- During Play, do not wear jewelry (rings, watches, necklaces, etc.). Objects may entangle in net or other areas of structure.
- Keep water and organic material away from pole. Pole can rust and fail.
- Once a month check pole and all metal parts for rust. Completely remove rust and repaint with exterior enamel. If rust has penetrated any steel part, replace that part immediately.
- Check system before each use for loose hardware, signs of rust and instability. Repair before each use. Never play on damaged equipment.
- Do not use this system to lift or hoist anything. The mechanism is designed to lift only the weight of the backboard and rim. Do not hang anything from the handle, rim, backboard, or lifter arms as this will damage the system and void the warranty.
- Refer to product manual for assembly instructions.

4L-8916-00

www.Goalrilla.com 1-888-USA-GOAL

SAFETY INSTRUCTIONS

FAILURE TO FOLLOW THESE SAFETY INSTRUCTIONS MAY RESULT IN SERIOUS INJURY, PROPERTY DAMAGE AND WILL VOID WARRANTY.

Owner must ensure that all players know and follow these rules for safe operation of the system.

To ensure safety, do not attempt to assemble this system without following the instructions carefully. Proper and complete assembly, use and supervision is essential for proper operation and to reduce the risk of accident or injury. A high probability of serious injury exists if this system is not installed, maintained, and operated properly.

- If using a ladder during assembly, use extreme caution.
- 4 people are recommended for this operation.
- Backboard installation must be performed by a professional with capable lifting equipment.
- Seat the pole sections properly (if applicable). Failure to do so could allow the pole sections to separate during play.
- Before digging contact utility company to locate underground power cables, gas and water lines. Ensure there are no overhead power lines within 20 ft. (7m) radius of pole location.
- Climate, corrosion or misuse could result in system failure.
- If technical assistance is required, contact our Customer Service department located on the cover page & page 2.

*Most injuries are caused by misuse and/or not following instructions.
Use caution when using this system.*

WARNING

FAILURE TO FOLLOW THESE WARNINGS MAY RESULT IN SERIOUS INJURY AND/OR PROPERTY DAMAGE.

- Only hang from the rim of GROUND BASED SYSTEMS briefly to regain balance or avoid injuring others. Release the rim as soon as possible.
DO NOT DUNK OR HANG ON WALLMOUNT SYSTEMS.
- During play, do not wear jewelry (rings, watches, necklaces, etc.)
Objects may entangle in net or other areas of structure.
- Wear mouth guard during playing to avoid dental injuries.
- Do not allow children to adjust the system.
- See mounting structure for additional warnings.

PARTS LIST (NOT ACTUAL SIZE)


NOTICE

DO NOT REMOVE THE PROTECTIVE FILM
ON THE UPPER BASE POLE UNTIL
INSTALLATION IS COMPLETE.


72" GLASS BACKBOARD
6A-7706-00
(QTY. 1)

OR


72" STEEL PERFORATED
BACKBOARD
6A-9165-00
(QTY. 1)




BOARD ARM CAP
3M-9465-00
(QTY. 1)




LOWER BASE POLE
1A-8025-00
(QTY. 1)



UPPER BASE POLE
1A-8026-00
(QTY. 1)




UPPER BOARD ARM - RIGHT
1A-8027-00
(QTY. 1)




UPPER BOARD ARM - LEFT
1A-8028-00
(QTY. 1)


ACCESSORIES (NOT ACTUAL SIZE)




UNIVERSAL POLE PAD
3M-8926-00
(QTY. 1)



BOARD PAD LEFT
3M-8904-00
(QTY. 1)




BOARD PAD CENTER
3M-8907-00
(QTY. 1)




BOARD PAD RIGHT
3M-8905-00
(QTY. 1)

RIM ASSEMBLY KIT IDENTIFIER


PARTS LIST (NOT ACTUAL SIZE)




BREAKAWAY RIM ASSEMBLY
6A-7825-00
(QTY. 1)




RIM COVER PLATE
2S-9467-00
(QTY. 1)



NET
3F-6010-00
(QTY. 1)




NET CABLE
2M-6915-00
(QTY. 1)




SET SCREW
1B-7266-00
(QTY. 2)


INCLUDED HARDWARE (ACTUAL SIZE)




3/8-16 X 1 3/4" CARRIAGE BOLT
1B-6782-10
(QTY. 4)




3/8-16 NYLOCK LOCKNUT
2B-6238-10
(QTY. 4)



3/8 X 19MM FLAT WASHER
2B-6289-10
(QTY. 4)




#8 X 1/2" THREAD CUTTING SCREW
1B-6238-01
(QTY. 4)




2.5 MM HEX KEY
7B-8579-00
(QTY. 1)

USED TOGETHER


HARDWARE IDENTIFIER (ACTUAL SIZE)




1/2-13 X 7 3/4" HEX BOLT
1B-7133-00
(QTY. 2)




1/2-13X1.75HHCS XLAN GR5 BLK
1B-6944-10
(QTY. 2)




5/16" HEX KEY SOCKET, 1/2" DRIVE
7B-8575-00
(QTY. 1)




1/2-13x1.5 Flat Socket
Cap Screw-Zinc
1B-7217-00
(QTY. 2)
(For Arm Assembly)




3/8-16 x 1" Button Head
Screw - Zinc
1B-7221-00
(QTY. 2)




1/2" FLAT WASHER
2B-6093-10
(QTY. 6)




TWO WAY STEP BUSHING
7B-6439-00
(QTY. 2)




1/2-13 NYLOCK LOCKNUT
2B-6095-10
(QTY. 4)




3/8 FLAT WASHER
2B-6289-10
(QTY. 20)



STEP BUSHING
7B-6391-01
(QTY. 2)




#10-32 x 3/4 THREAD
CUTTING SCREWS
1B-7271-00
(QTY. 4)




#10 X 1.75 SELF DRILLING /
SELF TAPPING SCREW
1B-6969-00
(QTY. 6)


ANCHOR KIT HARDWARE IDENTIFIER (ACTUAL SIZE)




5/8"-11 HEX NUT
2B-6097-02
(QTY. 12)



5/8" SPLIT LOCK
WASHER
2B-6099-02
(QTY. 4)




5/8" FLAT WASHER
2B-6098-03
(QTY. 8)




5/8" THREAD
PROTECTOR
PLASTIC CAP
3M-9040-00
(QTY. 4)

***Hardware located in Anchor kit box
(#29, #30, #31, #32)**

PARTS LIST (NOT ACTUAL SIZE)



ANCHOR PLATE
2S-6494-00
(QTY. 1)



5/8"-11 X 18 "J" BOLT
2B-6096-00
(QTY. 4)



#3 X 40" REBAR
1S-6152-00
(QTY. 4)

***Parts located in Anchor kit box (#33, #34 #35)**

INSTALLATION TIMELINE

1. Prior to anchor system and goal assembly, call utility services (811) for location of underground utility lines before you dig.
2. Vertical main post assembly is a two part process.

PART 1

Day 1. Complete Anchor System Installation Instructions. (Below)

Day 2-4. Allow concrete to cure.

PART 2

Day 5. Complete Goalrilla™ assembly instructions. (Requires four adults)

ANCHOR SYSTEM INSTALLATION INSTRUCTIONS (Day 1)



Before digging hole for anchor system, check for buried power, gas, water, and telecommunication lines! Failure to do so could result in serious or fatal injury! Contact your local utility company if unsure.

Items needed for Anchor Installation (not included)

- 11 - 80 lb. bags of concrete (2-3 extra recommended)
- 1 - post hole digger (optional)
- 1 - 15/16" open end wrench
- 1 - 15/16" socket and ratchet (optional)
- 1 - concrete form (see note after step 2)
- 1 - wheel barrow
- 1 - garden hose
- 1 - level
- 1 - tape measure

Note: For best results with less vibration, anchor system should be independent of court. If pouring concrete for both at same time, add an expansion joint in between.

Note: When digging hole, if you hit rock and cannot dig through contact a contractor.

1. Determine the desired location of the backboard over the playing court. From that location, use the overhang distance of 60" (5ft) to determine the correct location of the anchor system. See **Figure 1**.




Figure 1

2. Assemble anchor system as follows: Thread nuts (#29) to the bottom of threads of 4 J Bolts (#34). Insert threads of J Bolts (#34) up through holes on the anchor plate (#33) and secure with nuts (#29). See **Figure 2**.

Note: Each leg of J Bolts should face the anchor bolt to the right. See **Detail A**.

Detail A Bottom View





Figure 2



ANCHOR SYSTEM INSTALLATION INSTRUCTIONS (Day 1)

NOTE: Using a concrete form for the top 4" of the concrete is recommended. Cardboard forms can be purchased at some hardware and home stores or a wooden form can be constructed out of 2 x 4's.

NOTE: Failure to dig and fill the hole as instructed will result in increased system vibration.

***Tip:** It is always a good idea to purchase one or two extra bags of concrete, just in case you need them. If extra bags are not used you can return them to the store.

3. Mix and pour concrete into the hole. Follow instructions on the concrete bag. Stop about 18" below court level.
4. Insert four pieces Rebar (#35) into concrete 8" apart creating a square in the center of the hole.
5. Place the concrete form in the desired location and finish pouring concrete up to and even with the court level.
6. Push anchor system into concrete and agitate to work out voids in concrete. Immediately use a level to level the anchor plate and then square the anchor plate to the playing surface. Clean off any concrete that may be on exposed threads.

NOTE: The bottom four nuts will be forever embedded in concrete. The top four nuts remain on bolts and are used for leveling. (See Step 1 on page 10)


Let concrete cure for a MINIMUM of 72 hours.

⚠ IMPORTANT ⚠


The top surface of the concrete should be level with the playing surface (Court) to make sure the hoop is at 10' once installation is complete.

Figure 3

Top View




IMPORTANT




IMPORTANT

HARDWARE NEEDED (ACTUAL SIZE)




5/8"-11 HEX NUT, BLACK
2B-6097-02
(QTY. 4)



5/8" SPLIT LOCK
WASHER, BLACK
2B-6099-02
(QTY. 4)




5/8" FLAT WASHER, BLACK
2B-6098-03
(QTY. 8)



5/8" THREAD
PROTECTOR
PLASTIC CAP
3M-9040-00
(QTY. 4)

*Hardware located in Anchor kit box

TOOLS NEEDED




15/16"

OR



15/16"



Level



WARNING


PLACING THE POST ON THE ANCHOR SYSTEM
REQUIRES AT LEAST THREE CAPABLE ADULTS.
POLE WILL WANT TO LEAN WHILE ATTEMPTING TO
STAND IT UP ON J BOLTS.

NOTICE


**DO NOT REMOVE BOTTOM NUTS #29 THAT
YOU INSTALLED IN STEP 2 (PAGE 8).**

Let concrete cure for a
MINIMUM of 72 hours
before installing pole.

NOTE: Warning label on
lower base pole should face
away from playing court.



15/16" socket or
Box end wrench



DETAIL A

NOTE:

If basketball system needs to be
moved, **do not** try to salvage
caps. Caps #32 will be tight,
please remove with pliers and
discard. New caps will come in
new anchor system.

NOTE:

If #32 caps are missing for any
reason please call customer service.

NOTE:


Bottom nuts #29 can be used for
leveling system. See Step 1.

GOALRILLA ASSEMBLY INSTRUCTIONS (Day 5)

1. Lift lower pole (#2) and place onto the anchor system and secure with hardware as shown. Tighten Fasteners finger tight, leave loose enough to level pole. Place a level on pole and adjust bottom nuts (#29) until pole is level (left to right and front to back). Tighten top four hex nuts (#29) tight. Check pole again, front/back and side/side, to make sure the pole is level. Adjust the bottom nuts 29 as required. Tighten tight when complete.
2. Push on Thread Protector Cap (#32) until it is securely in place. Cap may be tight, push hard but **DO NOT** hit with a hammer! See Detail A.


HARDWARE NEEDED (ACTUAL SIZE)

TOOLS NEEDED




1/2-13x1.5 Flat Socket
Cap Screw-Zinc
1B-7217-00

QTY. 2




3/8-16 x 1" Button
Head Screw - Zinc
1B-7221-00

QTY. 2




#10-32 X 3/4 Thread
Cutting Screws
1B-7271-00
(QTY. 4)

5/16" Hex Key
Socket, 1/2" Drive
(Included)



1/2" Drive Torque
Wrench and
included 5/16"
Hex Key socket




Phillips


Use Together

NOTICE
DO NOT REMOVE THE PROTECTIVE FILM ON THE
UPPER BASE POLE UNTIL INSTALLATION IS COMPLETE.


1. With the help of another adult, place the Upper Base Pole (#3) on top of the Lower Pole (#2). Install Top bolts (#22) as shown in **Detail A**. Tighten bolts, tight.
2. Install Bottom Bolts (#23) as shown in **Detail B**. Tighten bolts, tight.
3. Tighten Top Bolts (#22) to 90FT-lbs with a torque wrench and included 5/16" socket (#21).
4. Install Board Arm Cap (#4) onto the Upper Base Pole (#3) using screws (#36) as shown in **Detail C**.




DETAIL A



DETAIL B




DETAIL C




5. Attach Right Arm (#5) & Left Arm (#6) as shown in **Detail A**. Hand tighten only until instructed to tighten them.

NOTICE

DO NOT REMOVE THE PROTECTIVE FILM ON THE UPPER BASE POLE UNTIL INSTALLATION IS COMPLETE.



DETAIL A



Important: Water drain holes MUST be on the bottom side.


Attaching metal net cable to the rim.

1. Place the Rim on a Non-Abrasive table upside down and locate the small cable tubes. See **Figure 1 & Detail A**.


2. Insert the net cable through the **first cable tube**. See **Detail A**.

NOTE: Using needle nose pliers is recommended to make it easier to hold and pull the net cable through the small metal tubes but it is not required.


3. Hold on to the end of the net cable then pull out until there's a couple of inches of slack. See **Detail B & Detail C**.




DETAIL A



DETAIL B



DETAIL C




Attaching net to the rim.


4. Pick a loop on the nylon rim net and put it through the net cable as shown in **Detail A** & **Detail B**.

Note: Make sure there are no twists in net loops.


5. Slowly pull the net cable back until there is no slack, but make sure the net loop does not slip off. Then, insert and push the cable into the next cable tube. See **Detail C**.




DETAIL A



DETAIL B



DETAIL C



Tighten the Set Screws

6. Repeat steps 1-5 until all the net loops are through the net cable and the net cable is through all the cable tubes. See **Figure 3** & **Detail A**.

NOTE: Using needle nose pliers is recommended to make it easier to hold and pull the net cable through the small metal tubes but it is not required.

7. Insert the set screws (**#38**) into the threaded holes in the small cable tubes and tighten tight using the Allen key (**#39**). See **Detail B**.







FIGURE 3




Inserting top Carriage Bolts to top rim slots.

8. Insert the **top Carriage Bolts (#15)** into the carriage bolt holes located at the top back of the rim. See **Figure 4**.



9. Slide the Carriage Bolts (#15) outward into the slots as shown below. Carriage Bolts should stay in place to aid installation on the next step. See **Detail A**.



Mounting Goal Assembly to the backboard.

1. Open lid of box containing backboard (#1).
With the help of another capable adult rotate the backboard upright to a vertical position.

Note: Do not take Backboard out of the box. Use the cardboard box under backboard to protect backboard paint from scratches.

Optional to Steps 2 and 3.

Helpful Hint: Carefully place the Backboard horizontally on 2 Heavy Duty saw-horses, Glass side up to attach the rim and then jump ahead to page 25 and attach backboard pads per instructions.

2. While one capable person holds the backboard, have a second person attach the rim up to the backboard with the **top Carriage Bolts** (#15) installed in the previous step and slide them into the holes in backboard as shown in **Detail A**. While still holding the rim up from the front reach around behind the rim and attach the Washers (#16) and Nuts (#17) as shown in **Detail A**.

NOTE: Tighten top nuts (#17) but leave loose enough to level Rim in a later step.



3. Insert the two **bottom** carriage bolts and attach washers (#16) and nuts (#17).

NOTE: Tighten bottom nuts (#17) but leave loose enough to level Rim in a later step.


! CAUTION

NEVER LOOSEN ANY NUTS OR BOLTS THAT HOLD THE BREAKAWAY RIM SPRING IN PLACE! THESE ARE UNDER SPRING LOAD AND COULD CAUSE DAMAGE TO PRODUCT/INJURY TO USER.


TOOLS NEEDED



NOTE: NET NOT SHOWN FOR CLARITY.




HARDWARE NEEDED (ACTUAL SIZE)



TWO WAY STEP BUSHING
7B-6439-00
(QTY. 2)

4. If not already installed, insert bushings (#25) as shown in **Detail A**.




Bushings inside
mounting brackets

NOTICE

IF THE BOARD BUSHINGS (#25) ARE NOT ALREADY PRE-INSTALLED INSERT AS SHOWN IN DETAIL A.

DETAIL A


Install two way step bushings #25 on the **INSIDE** of backboard mounting brackets.



Important: Bushings must be installed inside of mounting brackets.




IT IS RECOMMENDED THAT THE FOLLOWING STEPS ARE DONE BY A PROFESSIONAL WITH CAPABLE EQUIPMENT. PLEASE TAKE PROPER SAFETY MEASURES WHEN ATTACHING THE BACKBOARD TO UPPER ARM.




Before proceeding to the next step have the hardware and tools ready along with professional equipment. Read the next page completely and understand it before beginning the next step.

TOOLS NEEDED




3/4"




3/4"


HARDWARE NEEDED (ACTUAL SIZE)




1/2-13 X 7 3/4" HEX BOLT
1B-7133-00
(QTY. 1)



1/2-13 NYLOCK LOCKNUT
2B-6095-10
(QTY. 3)



STEP BUSHING
7B-6391-01
(QTY. 2)




1/2" FLAT WASHER
2B-6093-10
(QTY. 6)

⚠ DANGER

THE FOLLOWING STEPS MUST BE COMPLETED BY A PROFESSIONAL WITH CAPABLE LIFTING EQUIPMENT. PLEASE TAKE PROPER MEASURES WHEN ATTACHING THE BACKBOARD TO UPPER BASE POLE. BE PREPARED TO ATTACH THE UPPER BOARD ARMS IMMEDIATELY AFTER ATTACHING THE BACKBOARD TO THE UPPER BASE POLE.

1. Raise the backboard assembly up and attach Upper Base Pole (#3) to **rim support** as shown in **Detail A**. Fully tighten the hardware until the Backboard is secure. Proceed to the next step **immediately** and attach the upper board arms to the backboard.




⚠ DANGER

EXTREMELY HEAVY BACKBOARD! HANDLE WITH CARE, IT IS A GLASS PRODUCT. ALWAYS WEAR SAFETY GLASSES AND GLOVES WHEN HANDLING GLASS. DEATH OR SERIOUS INJURY CAN OCCUR WITHOUT CAPABLE LIFTING EQUIPMENT.

⚠ DANGER


THE BACKBOARD WILL PIVOT UNTIL THE UPPER BOARD ARMS ARE INSTALLED. DO NOT LEAVE THE SYSTEM UNATTENDED UNTIL THE UPPER BOARD ARMS ARE ATTACHED AND SECURED.



DANGER

THE BACKBOARD WILL PIVOT UNTIL THE UPPER BOARD ARMS ARE INSTALLED. DO NOT LEAVE THE SYSTEM UNATTENDED UNTIL THE UPPER BOARD ARMS ARE ATTACHED AND SECURED.

2. Carefully swing the upper board arms up as shown in **Detail A**.
3. Attach upper **board arms** to the inside of the **upper mounting brackets** and step bushings as shown in **Detail B**. Tighten all hardware fully at this time.





NOTICE


AT THIS TIME, CAREFULLY REMOVE THE PROTECTIVE FILM FROM THE UPPER BASE POLE

DANGER

EXTREMELY HEAVY BACKBOARD! HANDLE WITH CARE, IT IS A GLASS PRODUCT. ALWAYS WEAR SAFETY GLASSES AND GLOVES WHEN HANDLING GLASS. DEATH OR SERIOUS INJURY CAN OCCUR WITHOUT CAPABLE LIFTING EQUIPMENT.




HARDWARE NEEDED (ACTUAL SIZE)



#8 X 1/2" THREAD CUTTING SCREW
1B-6238-01

(QTY. 4)

TOOLS NEEDED



Level



Cordless Drill



Phillips
#2 Bit



4. Place Level across the Goal Assembly and adjust until level. Finish tightening the four (#17) nuts on the back of the Goal assembly until Goal Assembly is secure.
5. Attach Rim Cover Plate (#12) with four screws (#18).

! CAUTION

NEVER LOOSEN ANY NUTS OR BOLTS THAT HOLD THE BREAKAWAY RIM SPRING IN PLACE! THESE ARE UNDER SPRING LOAD AND COULD CAUSE DAMAGE TO PRODUCT/INJURY TO USER.

! CAUTION


NEVER USE RIM WITH COVERPLATE REMOVED!



Cover Plate

Phillips driver
required

TOOLS NEEDED



Level



15/16"


NOTICE

TWO ADULTS ARE RECOMMENDED FOR THIS STEP, ONE TO LEVEL AND ONE TO ADJUST THE BOTTOM #29 NUTS.

6. If further leveling is required, loosen the top (#29) nuts but do not loosen past the top of (#34) "J" Bolt. **DO NOT REMOVE NUTS #29.** Place a level on pole and adjust bottom nuts (#29) with a 15/16" open end wrench until pole is level. Tighten top (#29) hex nuts. See **Detail A**.


NOTE: At this time, measure the height of the rim. If the rim height is not 10', the system can be raised by adjusting the top nuts (#29) and bottom nuts (#29) until the 10' height is reached. The top nut (#29) should not be raised past the top of the J-bolts (#34). Once the 10' height is reached, the system should be leveled by following Step 6.

NOTE: The correct rim height should measure 10' from the top of the rim down to the playing court.



NOTE: Minor Left to Right and Front to back Backboard and Rim adjustments can be made using the instructions in step #6 and the "Note" above.


DETAIL A





15/16" socket or Box end wrench

15/16" open end wrench

7. Secure Post Pad (#7) to front of pole by wrapping straps around the back pole and sticking to velcro on opposite side of pad as shown.



Important Note: Cordless Drill and board pad screws must be drilled in **straight** to avoid shattering the backboard glass.



Note: Part (#10) is a Right Backboard pad & (#8) is a Left Backboard pad.

Note: Safety glasses required for Step 8.

Note: A Cordless drill is required for screws (#37) installation. Do not over tighten screws causing screws to strip.

Note: To install screws, you must use a cordless drill with a 5/16" socket.

8. Secure Backboard pads (#8) first, (#9) second and (#10) last using screws (#37) as shown.

Note: Screws (#37) are self-drilling and self-tapping. While holding each board pad in its correct position on the edge of the backboard, hold the drill and screw straight and drill through the aluminum trim and then continue through one side of the steel frame. Tighten, but do not overtighten the screws.

CARE AND MAINTENANCE

BACKBOARD CARE AND MAINTENANCE

Items needed to clean backboard:

- 100% cotton soft cloth, (only)
- Ammonia-free glass cleaner

Clean backboard using only a **100% Cotton** soft cloth and Ammonia-free glass cleaner. Clean glass as you would clean household windows. Strong cleansers will damage backboard and void the warranty.

RUST

Inspect your pole periodically, if rust should appear, remove loose paint, sand lightly, primer and paint with exterior flat matte finish enamel paint.

LIMITED LIFETIME WARRANTY

This consumer warranty extends to the original consumer purchase of any Escalade® Sports Product (hereinafter referred to as the "Product").

WARRANTY COVERAGE: Escalade® Sports warrants to the original Consumer Purchaser that any Product of its manufacture is free from defects in material and workmanship. THIS WARRANTY IS VOID IF THE PRODUCT HAS BEEN DAMAGED BY ACCIDENT, UNREASONABLE USE, NEGLIGENCE, IMPROPER SERVICE, FAILURE TO FOLLOW INSTRUCTIONS PROVIDED WITH THE PRODUCT OR OTHER CAUSES NOT ARISING OUT OF DEFECTS IN MATERIAL OR WORKMANSHIP.

Subject to proper installation and normal use, Escalade® Sports warrants, subject to the limitations below, to the original retail purchaser all structural components of the Goalrilla™ System to be free of defects in material and workmanship for the duration of ownership by the original retail purchaser.

Merchandise must be shipped prepaid with a copy of proof of purchase to Escalade® Sports factory for examination to determine if the basketball system needs to be repaired or replaced. Any labor costs, travel expenses and any other changes involved in the removal, installation or replacement of the defective/repared parts from/to your Goalrilla™ System will be the purchaser's responsibility. Shipping charges for replaced or warranted merchandise sent back to the customer from Escalade® Sports factory must be prepaid by the customer in advance. If not, the replacement shipment will be sent out collect.

Escalade® Sports reserves the right to examine photographs or physical evidence of merchandise claimed to be defective, and to recover said merchandise, prior to authorization of warranty claims. A "Returned Goods Authorization" number may be required, please call for details prior to the return of any photographs or merchandise.

This limited lifetime warranty is expressly in lieu of all warranties, expressed or implied, including warranties of merchantability or fitness for use. Escalade® Sports does not assume or authorize any person or representative to assume for us, any other liability in connection with the sale of our products.

The remedy of repair or replacement stated above is Escalade® Sports exclusive remedy. Escalade® Sports will not be liable for any other damages or expenses which may incur, including but not limited to incidental or consequential damages. Escalade® Sports assumes no other obligations or liability on the part of the purchaser, and Escalade® Sports neither assumes nor authorizes any other person to assume for it any other liability in connection with the goods sold.

This warranty shall not apply in any manner to parts or accessories not manufactured by Escalade® Sports.

NOT COVERED BY THIS WARRANTY

- Merchandise not intended to be in places of public assembly, such as, but not limited to, schools, parks, public or private recreational facilities.
- Any merchandise subjected to abuse, negligence, improper installation, vandalism, acts of God, alteration of product, or any other events beyond the control of Escalade® Sports.
- Paint or rusted parts. If rust should appear, remove loose paint, sand lightly, primer and paint with exterior flat matte finish enamel paint.
- Rims are not warranted for any defects other than workmanship. Torn back plates, damaged springs, bent rings, damaged eyebolts, and torn or distorted rim supports result from hanging on the rim and are not warranted.
- Shipping charges both ways. Note: Any merchandise shipped to Escalade® Sports collect will be refused.
- Dealer service charges, labor charges and travel expenses associated with replacement of repair of warranty item.
- Pole pads and backboard pads. These items are covered by 90-day warranties.

WARRANTY DISCLAIMERS: ANY IMPLIED WARRANTIES ARISING OUT OF THIS SALE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION. ESCALADE® SPORTS SHALL NOT BE LIABLE FOR LOSS OF USE OF THE PRODUCT OR OTHER CONSEQUENTIAL OR INCIDENTAL COSTS. EXPENSES OR DAMAGES INCURRED BY THE CONSUMER OF ANY OTHER USE.

Some states do not allow the exclusion or limitation of implied warranties or consequential or incidental damages, so the above limitations or exclusions may not apply to you.

LEGAL REMEDIES: This warranty gives you specific legal rights, and you may also have other rights which may vary from state to state.

WARRANTY GUIDELINES IS REQUIRED FOR ALL WARRANTY CLAIMS

1. Proof of Purchase (original retail purchaser) is required for all warranty claims.
 2. Call or write Escalade® Sports to receive a Return Authorization # and determine specific needs.
- Phone: 1-888-USA-GOAL / Warranty Dept.
Or Write Escalade® Sports at: Escalade® Sports - P.O. Box 889, Evansville, IN 47706 - Attn: Warranty Dept.
Or E-mail us at: customerservice@escaladesports.com